

Jointly Extracting Event Triggers and Arguments by Dependency-Bridge RNN and Tensor-Based Argument Interaction

Feng Qian*, Lei Sha*, Baobao Chang, Zhifang Sui

Institute of Computational Linguistics, Peking University
{*nickqian, shalei, chbb, szf*}@pku.edu.cn

November 29, 2017

Table of Contents

- 1 Introduction
- 2 Motivations
- 3 Dependency bridges
- 4 Tensor for various arg-arg relationships
- 5 Experiments
- 6 Conclusion

Table of Contents


- 1 Introduction
- 2 Motivations
- 3 Dependency bridges
- 4 Tensor for various arg-arg relationships
- 5 Experiments
- 6 Conclusion

Introduction

- Event extraction is important for knowledge acquisition from large amounts of news text.
- The result of event extraction can be used to construct knowledge base, which can be applied to question answering, dialogue system, etc.
- Its paradigm is ubiquitous in our daily life:
 - Knowledge Graph
 - Structured summary of search engine
 - Wikipedia infobox

Applications of Event Extraction

The Google search result of *September 11 attacks*:



September 11 attacks



The September 11 attacks were a series of four coordinated terrorist attacks by the Islamic terrorist group al-Qaeda on the United States on the morning of Tuesday, September 11, 2001. [Wikipedia](#)

Date: September 11, 2001

Perpetrator: [Al-Qaeda](#)

Total number of deaths: 2,997 (2,978 victims + 19 hijackers)

Locations: [New York City](#), [Arlington County](#), [Stonycreek Township](#)

Attack types: [Aircraft hijacking](#), [Mass murder](#), [Suicide attack](#)


Applications of Event Extraction

The Wikipedia infobox of *September 11 attacks*:

<p>September 11 attacks Part of Terrorism in the United States</p>  <p><i>Top row:</i> The Twin Towers of the World Trade Center burning</p> <p><i>2nd row, left to right:</i> Collapsed section of the Pentagon; Flight 175 crashes into 2 WTC;</p> <p><i>3rd row, left to right:</i> A firefighter requests assistance at World Trade Center site; Ground Zero; An engine from Flight 93 is recovered</p> <p><i>Bottom row:</i> Flight 77's collision with the Pentagon as captured by three consecutive CCTV frames</p>	<table><tbody><tr><td>Location</td><td>New York City, New York, U.S.; Arlington County, Virginia, U.S.; Stonycreek Township near Shanksville, Pennsylvania, U.S.</td></tr><tr><td>Date</td><td>September 11, 2001; 15 years ago 8:46 a.m. – 10:28 a.m. (EDT)</td></tr><tr><td>Target</td><td>World Trade Center (AA11 and UA 175) The Pentagon (AA77) White House or U.S. Capitol (UA 93; failed)</td></tr><tr><td>Attack type</td><td>Aircraft hijackings Suicide attacks Mass murder Terrorism</td></tr><tr><td>Deaths</td><td>2,997 (2,978 victims + 19 hijackers)</td></tr><tr><td>Non-fatal injuries</td><td>6,000+</td></tr><tr><td>Perpetrators</td><td>Al-Qaeda^[1] (see also responsibility and hijackers)</td></tr><tr><td>No. of participants</td><td>19</td></tr></tbody></table>	Location	New York City, New York, U.S.; Arlington County, Virginia, U.S.; Stonycreek Township near Shanksville, Pennsylvania, U.S.	Date	September 11, 2001; 15 years ago 8:46 a.m. – 10:28 a.m. (EDT)	Target	World Trade Center (AA11 and UA 175) The Pentagon (AA77) White House or U.S. Capitol (UA 93; failed)	Attack type	Aircraft hijackings Suicide attacks Mass murder Terrorism	Deaths	2,997 (2,978 victims + 19 hijackers)	Non-fatal injuries	6,000+	Perpetrators	Al-Qaeda^[1] (see also responsibility and hijackers)	No. of participants	19
Location	New York City, New York, U.S.; Arlington County, Virginia, U.S.; Stonycreek Township near Shanksville, Pennsylvania, U.S.																
Date	September 11, 2001; 15 years ago 8:46 a.m. – 10:28 a.m. (EDT)																
Target	World Trade Center (AA11 and UA 175) The Pentagon (AA77) White House or U.S. Capitol (UA 93; failed)																
Attack type	Aircraft hijackings Suicide attacks Mass murder Terrorism																
Deaths	2,997 (2,978 victims + 19 hijackers)																
Non-fatal injuries	6,000+																
Perpetrators	Al-Qaeda^[1] (see also responsibility and hijackers)																
No. of participants	19																

Applications of Event Extraction

- The extracted events can be transferred into triples and store in the knowledge graphs.
- The knowledge graphs can be leveraged by upper applications.



Event Extraction

What's an event?



Event Type:	Business	
Trigger	Release	
Argument	Company	Microsoft
	Product	Surface Pro
	Place	USA

Figure: Microsoft releases surface Pro in USA.

Event Extraction

What's an event?



Event Type:	Attack	
Trigger	Crash	
Argument	Attacker	Five hijackers
	Target	World Trade Center's North Tower
	Instrument	American Airlines Flight 11
	Time	September 11th

Figure: On September 11th, five hijackers crashed American Airlines Flight 11 into the World Trade Center's North Tower.

Event Extraction from News Text

What should we do?

- Extract trigger
- Identify arguments
- Classify roles

Event Type:	Die	
Trigger	Die	
Argument	Victim	cameraman
	Place	Baghdad
	Instrument	American tank




Table of Contents

- 1 Introduction
- 2 Motivations**
- 3 Dependency bridges
- 4 Tensor for various arg-arg relationships
- 5 Experiments
- 6 Conclusion

Motivation

Challenges of event extraction by the previous solutions

- ✓ Using syntax information as feature
- × Using syntax information as architecture
- ✓ Capture two kinds of argument-argument relationship (Pos & Neg)
- × Capture large amount of argument-argument relationship

Table of Contents

- 1 Introduction
- 2 Motivations
- 3 Dependency bridges**
- 4 Tensor for various arg-arg relationships
- 5 Experiments
- 6 Conclusion

Event Extraction from News Text

Motivation 1:

- Dependency relation \rightarrow Dependency bridge
- According to definition of dependency relation, dependency edges usually contain some information about temporal, consequence, conditional or purpose.




Figure: Example of dependency parse tree.

Event Extraction from News Text

- We add dependency bridges to conventional LSTM-RNN architecture.
- Bidirectionality:
 - Forward: Set all dependency bridges as forward.
 - Backward: Set all dependency bridges as backward.




Figure: Dependency bridge on LSTM. Apart from the last LSTM cell, each cell also receives information from former syntactically related cells.

Event Extraction from News Text

Details of dependency bridge

- We add a new gate d_t and change the calculation of hidden state.
- $h_t = o_t \odot \tanh(c_t) + d_t \odot \left(\frac{1}{|S_{in}|} \sum_{(i,p) \in S_{in}} a_p h_i \right)$




Figure: The calculation detail of dependency bridge.

Table of Contents

- 1 Introduction
- 2 Motivations
- 3 Dependency bridges
- 4 Tensor for various arg-arg relationships**
- 5 Experiments
- 6 Conclusion

Event Extraction from News Text

Motivation 2:

- We represent each arg-arg relationship by a vector
- We use a tensor to represent all kinds of arg-arg relationships in a sentence




Figure: The calculation detail of tensor layer.

Event Extraction from News Text

The whole architecture ...

- Tensor layer is applied to the hidden layer of the dependency bridge RNN
- Then we apply max-pooling over arguments to find the most important “interactive features” for the arguments




Table of Contents

- 1 Introduction
- 2 Motivations
- 3 Dependency bridges
- 4 Tensor for various arg-arg relationships
- 5 Experiments**
- 6 Conclusion

Weights of each dependency relation




Figure: The visualization of trained weights of each dependency relations.

Overall performance

Method	Trigger Identification +Classification (%)			Argument Identification (%)			Argument Role (%)		
	P	R	F_1	P	R	F_1	P	R	F_1
Cross-Event	68.7	68.9	68.8	50.9	49.7	50.3	45.1	44.1	44.6
Cross-Entity	72.9	64.3	68.3	53.4	52.9	53.1	51.6	45.5	48.3
JointBeam	73.7	62.3	67.5	69.8	47.9	56.8	64.7	44.4	52.7
DMCNN	75.6	63.6	69.1	68.8	51.9	59.1	62.2	46.9	53.5
RBPB	70.3	67.5	68.9	63.2	59.4	61.2	54.1	53.5	53.8
JRNN	66.0	73.0	69.3	61.4	64.2	62.8	54.2	56.7	55.4
dbRTN	74.1	69.8	71.9	78.3	54.7	64.4	64.2	51.5	57.2

Figure: Performances of various approaches on ACE 2005 dataset.

Ablation tests – dependency bridge

- Binary DB: The weight of DB belongs to 0,1
- Typed DB: The weight of DB can be any float numbers

Method	Trigger id+cl	Argument id	Argument id+cl
Our model without DB	69.0	62.7	54.6
+ binary DB	71.2	63.9	56.8
+ typed DB (full)	71.9	64.4	57.2

Table: Comparison after adding dependency bridges (DB). The numbers are F_1 scores. We compare with two baselines: no dependency bridges considered and only binary dependency bridges.

Ablation tests – Tensor layer

- dbRNN-SMA: only cast SMA away from the whole model
- dbRNN-MP: means cast the max-pooling feature matrix away
- dbRNN-TL: dbRNN without tensor layer
- dbRNN full model

	Method	1/1	1/N	All
Argument Identification	dbRNN-SMA	59.5	67.0	64.1
	dbRNN-MP	59.7	64.8	62.0
	dbRNN-TL	59.6	55.8	58.2
	dbRNN	59.9	69.5	67.7
Argument Role Classification	dbRNN-SMA	54.6	56.5	56.0
	dbRNN-MP	54.7	55.8	55.2
	dbRNN-TL	54.9	52.3	53.1
	dbRNN	54.6	60.9	58.7

Table: Comparison between different models. Here, we report the argument performance since the tensor layer is only applied to argument extraction.

Table of Contents

- 1 Introduction
- 2 Motivations
- 3 Dependency bridges
- 4 Tensor for various arg-arg relationships
- 5 Experiments
- 6 Conclusion**

Conclusion

In this paper:

- We propose to add dependency bridges to sequential architecture
- We propose to add tensor layer for capturing various of argument relationships
- The weights of dependency bridges after training illuminates the importance of each dependency type in event extraction task
- The full model achieves high performance in all the three evaluation metrics, trigger classification, argument identification and role classification

Thank you. Any questions?